

Linerless paper High Quality 81g LLP 214

Facestock

A white top-coated thermal paper with high quality, providing a black thermo-sensitive image coating with standard sensitivity. Great resistance to fat, oil, water, alcohol, and plasticizer. The material is produced without any added Phenol. The paper has a siliconized surface.

This product offers a high performing, besides to be a sustainable solution for variable information.

Type
Paper

Image color Black	Printing speed (Max.) 200mm/s
-----------------------------	---

Properties	Method	Value
Basis Weight	ISO 536	81 ± 4g/m²
Caliper	ISO 534	78 ± 5µ

Regulatory Approval

BPA Free Yes	Top Coating Yes
------------------------	---------------------------

*Please contact your sales representative for details

Adhesive

A general purpose permanent adhesive designed for cutters or cutting equipment to prevent residue on the knife or set off on the platen roller.

LLP214 has good initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Not advised for labelling highly plasticized materials, e.g.: flexible PVC.

Composition Rubber	Composition Hot Melt	Type Permanent
Application Temperature 8 F	Min. Application Temperature -10 F	Max. Application Temperature 70 F

Properties	Method	Value
Typical Loop Tack (Filmic Substrate)	FTM9	18N/25mm

*Please contact your sales representative for details

Final product		
Format Roll		
Description	Method	Value
Typical Caliper	-	87 ± 3μ
Typical Loop Tack (Filmic Substrate)	FTM9	18N/25mm
Regulatory Approval		
Material Shelf Life		
Keep the material in the original packaging when not used in order to protect it from dust and contamination. 12 months stored at 20°C/50% RH non UV/Sunlight		
*Please contact your sales representative for details		

Last update: 02/20/2024

1. All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:
LINERLESS AB
Pål Anders Väg 6
SE-263 34 Höganäs - Sweden
sales.linerless@beontag.com or info.linerless@beontag.com