

Linerless

Rubber

Hot Melt

Paper

Linerless Paper Standard 76g LLP 214

Facestock

A white non-top-coated thermal paper, providing a black thermo-sensitive image with standard sensitivity. Good resistance to fat, oil, water and heat. The material is produced without any added Phenol. The paper has a siliconized surface.

This product offers a good performing, besides to be a sustainable solution for variable information.

Type

Paper

Image color

Black

Properties	Method	Value
Basis Weight	ISO 536	76 ± 6g/m ²
Caliper	ISO 534	71 ± 7μ

*Please contact your sales representative for details

Adhesive

A general purpose permanent adhesive designed for cutters or cutting equipment to prevent residue on the knife or set off on the platen roller.

LLP214 has good initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Not advised for labelling highly plasticized materials, e.g.: flexible PVC.

Composition Rubber	Composition Hot Melt	Type Permanent
Application Temperature 8 F	Min. Application Temperature -10 F	Max. Application Temperature 70 F
Properties	Method	Value
Typical Loop Tack (Filmic Substrate)	FTM9	20 N/25mm

*Please contact your sales representative for details

Final product

Format

Roll

Description	Method	Value
Typical Caliper	-	80 ± 5μ
Typical Loop Tack (Filmic Substrate)	FTM9	20 N/25mm

Regulatory Approval

Material Shelf Life

12 months stored at 20°C/50% RH non UV/Sunlight

*Please contact your sales representative for details

Last update: 02/20/2024

1. All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

LINERLESS AB

Pål Anders Väg 6

SE-263 34 Höganäs - Sweden

sales.linerless@beontag.com or info.linerless@beontag.com