

Linerless paper Top Coat 72g LLP 214

Facestock

A white top-coated thermal paper, providing a black thermo-sensitive image coating with standard sensitivity, very good resistance to fat, oil, water, alcohol and plasticizer. The material is produced without any added Phenol. The paper has a siliconized surface.

This product offers a good performing, besides to be a sustainable solution for variable information.

Type

Paper

Image color

Black

Printing speed (Max.)

250mm/s

Properties	Method	Value
Basis Weight	ISO 536	72 ± 6g/m²
Caliper	ISO 534	80 ± 8µ

*Please contact your sales representative for details

Adhesive

A general purpose permanent adhesive designed for cutters or cutting equipment to prevent residue on the knife or set off on the platen roller.

LLP214 has good initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Not advised for labelling highly plasticized materials, e.g.: flexible PVC.

Type

Permanent

Composition

Rubber

Composition

Hot Melt

Min. Application Temperature

8 F

Min. Service Temperature

-10 F

Max. Application Temperature

70 F

Properties	Method	Value
Typical Loop Tack (Filmic Substrate)	FTM9	20 N/25mm

*Please contact your sales representative for details

Final product

Description	Method	Value
Typical Caliper	-	89 ± 6µ

Material Shelf Life

12 months stored at 20°C/50% RH non UV/Sunlight

*Please contact your sales representative for details

Last update: 02/20/2024

- 1. All information, recommendations and descriptions of our products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty.
- 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition.
- 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:
LINERLESS AB
Pål Anders Väg 6
SE-263 34 Höganäs - Sweden
sales.linerless@beontag.com or info.linerless@beontag.com