

Pressure-sensitive adhesives

Acrylic

Paper

10 PT C1S TAG / IP400@ 1.7 Cwt. / 40#SCK L-10

ITEM #72353

Facestock

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers excellent stiffness and high internal strength.

Type

Paper

Tear MD205 Grams

Tear CD
200 Grams

Properties Value

Basis Weight 133lbs/3000 sq ft

Caliper 10.00 Mil

Brightness 94

Regulatory Approval

RoHSProp65REACHYesYesYes
TPCH
CPSIA
Yes
No

FSC No

Adhesive

A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.

| Type Permanent | Composition Acrylic | Shear 80 |
|--|--|--|
| Min. Application Temperature 35 F | Min. Service Temperature -65 F | Max. Application Temperature 200 F |
| Properties | Value | |
| Stainless Steel | 5.5 lbs/linear in. | |

^{*}Please contact your sales representative for details

Glass 3,2lbs/linear in.

Polyethylene 2

Corrugated 1.45 lbs./in.

Painted Metal 3.0 lbs/linear in.

Loop Tack 5.00 oz/in²

Regulatory Approval

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре

17142

Tensile MD Tensile CD

34 22

Tear MD Tear CD 32 34

DescriptionValueBasis Weight40Caliper2.5

Regulatory Approval

RoHSProp65REACHYesYesYes
TPCH
CPSIA
Yes
No

Direct Food

No

Last update: 05/01/2024

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com