

12 PT C1S TAG / TR1 @ 1.0 Cwt. / 40#SCK L-10

ITEM #87589

<p>FACESTOCK</p> <p>A premium coated one side stock with outstanding ink receptivity and print characteristics. This tag offers a 90 brightness, full double clay coating one side, high stiffness, excellent smoothness and gloss.</p>														
<p>Type Paper</p>														
<table border="1"> <thead> <tr> <th>PROPERTIES</th> <th>VALUE</th> </tr> </thead> <tbody> <tr> <td>Basis Weight</td> <td>123 # Rm 24 x 26</td> </tr> <tr> <td>Caliper</td> <td>12.00 Mil</td> </tr> <tr> <td>Brightness</td> <td>90</td> </tr> </tbody> </table>			PROPERTIES	VALUE	Basis Weight	123 # Rm 24 x 26	Caliper	12.00 Mil	Brightness	90				
PROPERTIES	VALUE													
Basis Weight	123 # Rm 24 x 26													
Caliper	12.00 Mil													
Brightness	90													
<p>REGULATORY APPROVAL</p> <table border="1"> <thead> <tr> <th>RoHS</th> <th>Prop65</th> <th>REACH</th> </tr> </thead> <tbody> <tr> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <th>TPCH</th> <th>CPSIA</th> <th>FSC</th> </tr> <tr> <td>Yes</td> <td>Yes</td> <td>No</td> </tr> </tbody> </table> <p>*Please contact your sales representative for details</p>			RoHS	Prop65	REACH	Yes	Yes	Yes	TPCH	CPSIA	FSC	Yes	Yes	No
RoHS	Prop65	REACH												
Yes	Yes	Yes												
TPCH	CPSIA	FSC												
Yes	Yes	No												

<p>ADHESIVE</p> <p>A specialty acrylic adhesive designed for clean removability from plastics and painted metal. Not recommended for curved or textured surfaces.</p>														
<table border="1"> <thead> <tr> <th>Type</th> <th>Composition</th> <th>Shear</th> </tr> </thead> <tbody> <tr> <td>Removable</td> <td>Acrylic</td> <td>35</td> </tr> <tr> <th>Min. Application Temperature</th> <th>Min. Service Temperature</th> <th>Max. Application Temperature</th> </tr> <tr> <td>40 F</td> <td>-65 F</td> <td>120 F</td> </tr> </tbody> </table>			Type	Composition	Shear	Removable	Acrylic	35	Min. Application Temperature	Min. Service Temperature	Max. Application Temperature	40 F	-65 F	120 F
Type	Composition	Shear												
Removable	Acrylic	35												
Min. Application Temperature	Min. Service Temperature	Max. Application Temperature												
40 F	-65 F	120 F												
<table border="1"> <thead> <tr> <th>PROPERTIES</th> <th>VALUE</th> </tr> </thead> <tbody> <tr> <td>Stainless Steel</td> <td>1.8 lbs/linear in.</td> </tr> <tr> <td>Glass</td> <td>0lbs/linear in.</td> </tr> <tr> <td>Corrugated</td> <td>0.55 lbs./in.</td> </tr> <tr> <td>Painted Metal</td> <td>1.3 lbs/linear in.</td> </tr> <tr> <td>Loop Tack</td> <td>1.35 oz/in²</td> </tr> </tbody> </table>			PROPERTIES	VALUE	Stainless Steel	1.8 lbs/linear in.	Glass	0lbs/linear in.	Corrugated	0.55 lbs./in.	Painted Metal	1.3 lbs/linear in.	Loop Tack	1.35 oz/in ²
PROPERTIES	VALUE													
Stainless Steel	1.8 lbs/linear in.													
Glass	0lbs/linear in.													
Corrugated	0.55 lbs./in.													
Painted Metal	1.3 lbs/linear in.													
Loop Tack	1.35 oz/in ²													
<p>REGULATORY APPROVAL</p> <table border="1"> <thead> <tr> <th>RoHS</th> <th>Prop65</th> <th>REACH</th> </tr> </thead> <tbody> <tr> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> </tbody> </table>			RoHS	Prop65	REACH	Yes	Yes	Yes						
RoHS	Prop65	REACH												
Yes	Yes	Yes												

TPCH
Yes

CPSIA
Yes

Direct Food
No

Indirect Food
Yes

*Please contact your sales representative for details

LINER

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type
17142

Tensile MD
34

Tensile CD
22

Tear MD
32

Tear CD
34

DESCRIPTION

VALUE

Basis Weight

40

Caliper

2.5

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426

[800-358-4448](tel:800-358-4448)

orders.us@beontag.com