

Pressure-sensitive adhesives

Acrylic Paper

17.25" X 22.25" MATTE LITHO / PERMANENT / 80# SCOREBACK L-3

ITEM #SC-002

Facestock

A premium matte litho stock with excellent ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face comes with a brightness of 84% and an opacity of 93%.

Туре			
Paper			
Tear MD	Tear CD		
50 Grams	55 Grams		
Properties	Value		
Basis Weight	60lbs/3300 sq ft		
Caliper	3.90 Mil		
Opacity	93		
Brightness	84		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	
*Please contact your sales representative for details			

Adhesive

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Type Permanent	Composition Acrylic
Properties	Value
Glass	2.8 lbs/linear in.
Polyethylene	1.5

Regulatory Appro	oval	
-------------------------	------	--

RoHS	Prop65	REACH		
Yes	Yes	Yes		
TPCH	CPSIA	Direct Food		
Yes	Yes	Yes		
Indirect Food Yes				
*Please contact your sales representative for details				

Liner

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

Type 9019084			
Tensile MD 36	Tensile CD 21		
Tear MD 61	Tear CD 71		
Description	Value		
Basis Weight	72		
Caliper	4.6		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
TPCH Yes	CPSIA Yes	UL No	
162	ies	INO	

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com