

Pressure-sensitive adhesives

Rubber Film

2.6 MIL WHITE TT BOPP / TL250 @ 2.5 Cwt. / 50#SCK L-3

ITEM #86650

Facestock

A 2.6 Mil matte white polypropylene film that is designed for thermal transfer printability. Features good weather resistance and dimensional stability.

Туре			
Film			
Tensile MD	Tensile CD		
13800	26800		
Elong MD	Elong CD		
170	55		
Properties	Value		
Caliper	2.6 mil		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	
*Please contact your sales represe	entative for details		

Adhesive

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

Type Permanent	Composition Rubber
Properties	Value
Glass	6,7lbs/linear in.
Polyethylene	7,5
Regulatory Approval	

RoHS	Prop65	REACH	
Yes	Yes	Yes	
TPCH	CPSIA	UL	
Yes	Yes	No	
Direct Food No	Indirect Food Yes		
*Please contact your sales repr	resentative for details		

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре			
5517353			
Tensile MD	Tensile CD		
40	24		
Tear MD	Tear CD		
44	48		
Description	Value		
Basis Weight	50		
Caliper	3.2		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
Direct Food			
No			
*Diana contact your color rest	poptativo for datailo		
*Please contact your sales repre			

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>