

26" X 20" MATTE LITHO / PERMANENT / 80# ZERO SCORE L-3

ITEM #SC-072

Facestock

A premium matte litho stock with excellent ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face comes with a brightness of 84% and an opacity of 93%.

Type

Paper

Tear MD

50 Grams

Tear CD

55 Grams

Properties	Value
Basis Weight	60lbs/3300 sq ft
Caliper	3.90 Mil
Opacity	93
Brightness	84

Regulatory Approval

RoHS

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

FSC

No

*Please contact your sales representative for details

<div><div>Adhesive</div><div>A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.</div></div>							
<div><div><div>Type</div><div>Permanent</div></div><div><div>Composition</div><div>Acrylic</div></div></div>							
<table><tr><th>Properties</th><th>Value</th></tr><tr><td>Glass</td><td>2.8 lbs/linear in.</td></tr><tr><td>Polyethylene</td><td>1.5</td></tr></table>		Properties	Value	Glass	2.8 lbs/linear in.	Polyethylene	1.5
Properties	Value						
Glass	2.8 lbs/linear in.						
Polyethylene	1.5						

Regulatory Approval		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	Direct Food Yes
Indirect Food Yes		
*Please contact your sales representative for details		

Liner A bleached kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting and butt-cutting.	
Type 9019086	
Tensile MD 51	Tensile CD 0
Tear MD 0	Tear CD 0
Description	Value
Basis Weight	72
Caliper	4.6
Regulatory Approval	
RoHS Yes	Prop65 Yes
TPCH Yes	CPSIA Yes
Direct Food No	REACH Yes
	UL No
*Please contact your sales representative for details	

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426

[800-358-4448](tel:800-358-4448)
orders.us@beontag.com