

Pressure-sensitive adhesives

Acrylic Paper

## 26" X 20" PREMIUM UNCOATED OFFSET / PERMANENT / 80# ZERO SCORE L-3

## ITEM #SC-077

<b>Facestock</b> A premium 98 Bright White offset sheet that is excellent for all high end offset printing.				
<b>Type</b> Paper				
Properties	Value			
Basis Weight	60 # Rm 25 x 38			
Caliper	4.20 Mil			
Opacity	94			
Brightness	98			
Regulatory Approval				
RoHS	Prop65	REACH		
Yes	Yes	Yes		
ТРСН	CPSIA	FSC		
Yes	Yes	No		
*Please contact your sales representative for details				

## Adhesive

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

<b>Type</b> Permanent	<b>Composition</b> Acrylic
Properties	Value
Glass	2.8 lbs/linear in.
Polyethylene	1.5
Regulatory Approval	

<b>RoHS</b>	<b>Prop65</b>	<b>REACH</b>		
Yes	Yes	Yes		
<b>TPCH</b>	<b>CPSIA</b>	<b>Direct Food</b>		
Yes	Yes	Yes		
Indirect Food Yes				
*Please contact your sales representative for details				

## Liner

A bleached kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting and butt-cutting.

<b>Type</b> 9019086			
<b>Tensile MD</b> 51	<b>Tensile CD</b> 0		
<b>Tear MD</b> 0	<b>Tear CD</b> 0		
Description	Value		
Basis Weight	72		
Caliper	4.6		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
<b>Direct Food</b> No			
*Please contact your sales representative for details			

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> orders.us@beontag.com