

Pressure-sensitive adhesives

Acrylic

# 4 MIL FLEXIBLE NTC VINYL / TS523 @ 1.5 Cwt. / 100# TAG L-3

ITEM #4898

#### **Facestock**

A 4 Mil white non top coated vinyl with polymeric plasticizers, formulated to provide optimum performance with pressure sensitive adhesives.

### **Type**

Film

**Tensile MD Tensile CD** 3900 lb/in 3800 lb/in **Tear MD Tear CD** 100 Grams 100 Grams

**Properties** Value

Caliper 4.0

# **Regulatory Approval**

**RoHS REACH** Prop65 Yes Yes Yes **TPCH CPSIA FSC** Yes Yes No

## **Adhesive**

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

Type	Composition	Shear 250
Permanent	Acrylic	350
BAC A I' T T	Min On the Towns and Institute	NA A I'-

**Min. Application Temperature Max. Application Temperature** Min. Service Temperature 200 F 35 F

-65 F

Properties	Value
Stainless Steel	5.6 lbs/linear in.
Glass	2,8lbs/linear in.

<sup>\*</sup>Please contact your sales representative for details

Polyethylene 2.9

Corrugated 1.50 lbs./in.

Painted Metal 4.9 lbs/linear in.

**Loop Tack** 2.70 oz/in<sup>2</sup>

### **Regulatory Approval**

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes No

#### **Indirect Food**

Yes

#### Liner

A 100# tag liner which has been silicone coated one side to give a controlled release. It has exceptionally high internal strength to withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes.

Tensile MD	Tensile CD
ICHSIIC IVID	ichishe ob

70 32

**Tear MD**130
Tear CD

Description	Value
Basis Weight	0
Caliper	8

## **Regulatory Approval**

RoHSProp65REACHYesYesYes

TPCH CPSIA
Yes Yes

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

<sup>\*</sup>Please contact your sales representative for details

<sup>\*</sup>Please contact your sales representative for details

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com