beontag

Pressure-sensitive adhesives | Rubber | Film

4 MIL YELLOW VINYL / TL250 @ 2.5 Cwt. / 50#SCK L-3

ITEM #84878

Facestock

A 4 mil yellow vinyl face sheet with consistent lay flat and gauge control for high tech label application. Polymeric plasticizers formulated to provide optimum performance with pressure sensitive adhesives.

Type
Film

Tensile MD
3300 lb/in

Tensile CD
2900 lb/in

Elong MD
100

Elong CD
150

Properties	Value
Caliper	4

Regulatory Approval

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

FSC
No

*Please contact your sales representative for details

Adhesive

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

Type
Permanent

Composition
Rubber

Properties	Value
Glass	6,7lbs/linear in.
Polyethylene	7,5

Regulatory Approval

RoHS

Prop65

REACH

Yes

Yes

Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

Indirect Food
Yes

*Please contact your sales representative for details

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type
5517353

Tensile MD
40

Tensile CD
24

Tear MD
44

Tear CD
48

Description	Value
Basis Weight	50
Caliper	3.2

Regulatory Approval

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.
BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com