

Pressure-sensitive adhesives

Latex Paper

55# HIBRIGHT SemiGloss / AP151@ 1.3 Cwt. / 1.2 MIL PET L-3

ITEM #88004

Facestock

A premium semigloss calendar coated one side stock with excellent ink receptivity and print characteristics. This stock offers an 88% brightness has an 87% opacity and a 70% gloss rating.

Туре					
Paper					
Tensile MD	Tensile CD				
35 Lbs/in	16 Lbs/in Tear CD				
Tear MD					
35 Grams	38 Grams				
Properties	Value				
Basis Weight	55				
Caliper	2.80 Mil				
Opacity	87				
Brightness	88				
Regulatory Approval					
RoHS	Prop65	REACH			
Yes	Yes	Yes			

Adhesive

TPCH

Yes

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

FSC

No

CPSIA

Yes

Type	Composition	Shear
Permanent	Latex	80
Min. Application Temperature	Min. Service Temperature	Max. Application Temperature
35 F	-65 F	220 F

D			
Properties	Value		
Stainless Steel	7.3 lbs/linear in.		
Glass	5.7 lbs/linear in.		
Polyethylene	6.5		
Corrugated	2.50 lbs./in.		
Painted Metal	7.0 lbs/linear in.		
Loop Tack	5.00 oz/in²		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	Direct Food	
Yes	Yes	No	
Indirect Food			
Yes			
*Please contact your sales repr	esentative for details		

Liner

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Tensile MD 30000 Tear MD 0	Tensile CD 0 Tear CD 0
Description	Value
Basis Weight	0
Caliper	1,2

Regulatory Approval

RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA		
Yes	Yes		
*Please contact your sales repre	esentative for details		

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>