

Pressure-sensitive adhesives

Acrylic

Paper

# 55# HIBRIGHT SemiGloss / TP170/LPG / 40#SCK L-3



ITEM #88278

## **Facestock**

A premium semigloss calendar coated one side stock with excellent ink receptivity and print characteristics. This stock offers an 88% brightness, has an 87% opacity and a 70% gloss rating

## Type

Paper

Tensile MD
35 Lbs/in
16 Lbs/in

Tear MD
Tear CD
35 Grams
35 Grams

Properties Value

Basis Weight 55

Caliper 2.80 Mil

# **Regulatory Approval**

RoHSProp65REACHYesYesYes
TPCH
Yes
CPSIA
Yes
Yes
Yes

### **Adhesive**

A general purpose acrylic adhesive showing good initial tack with high shear and high ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Туре	Composition	Shear
Permanent	Acrylic	300
<b>Min. Application Temperature</b> 35 F	<b>Min. Service Temperature</b> -65 F	<b>Max. Application Temperature</b> 180 F
Properties	Value	
Stainless Steel	5.2 lbs/linear in.	

<sup>\*</sup>Please contact your sales representative for details

**Glass** 3,2lbs/linear in.

Polyethylene 1.6

Corrugated 1.40 lbs./in.

Painted Metal 5.2 lbs/linear in.

**Loop Tack** 2.20 oz/in<sup>2</sup>

# **Regulatory Approval**

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes No

#### **Indirect Food**

Yes

## Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

## **Type**

5517342

Tensile MD Tensile CD

34 22

Tear MD Tear CD 32 34

DescriptionValueBasis Weight40Caliper2.5

# **Regulatory Approval**

RoHSProp65REACHYesYesYesTPCHCPSIAULYesYesNo

#### **Direct Food**

No

Last update: 08/21/2024

<sup>\*</sup>Please contact your sales representative for details

<sup>\*</sup>Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com