

Pressure-sensitive adhesives

Acrylic

Paper

60# CLASSIC CREST SOLAR WHITE WS / IP400 @ 1.7 Cwt. / 1.2 MIL PET L-3

ITEM #78883

Facestock

60# Fine Textured uncoated paper face sheet with internal wet strength properties. Most commonly used for wine label that is exposed to cold wet conditions.

Туре

Paper

Tensile MD
9 Lbs/in
6 Lbs/in

Tear MD
67 Grams
59 Grams

Properties	Value
Basis Weight	60 # Rm 25 x 38
Caliper	4.30 Mil
Opacity	90
Brightness	91

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	FSC
Yes	Yes	No

^{*}Please contact your sales representative for details

Adhesive

A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.

Type Permanent	Composition Acrylic	Shear 80
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 200 F

roperties	Value	
Stainless Steel	5.5 lbs/linear in.	
Glass	3,2lbs/linear in.	
Polyethylene	2	
Corrugated	1.45 lbs./in.	
Painted Metal	3.0 lbs/linear in.	
oop Tack	5.00 oz/in²	
Regulatory Approval		
RoHS	Prop65	REACH
10110	Yes	Yes
/es	100	
	CPSIA	Direct Food
/es		Direct Food No
/es 「PCH /es	CPSIA	
/es 「PCH	CPSIA	

Liner

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

ensile MD	Tensile CD		
30000	0		
Tear MD	Tear CD		
0	0		
Description	Value		
Basis Weight	0		
Caliper	1,2		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
TPCH	CPSIA		
Yes	Yes		

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com