

60# MATTE LITHO / TR447 @ 1.4 Cwt. / 40#SCK L-3

ITEM #211

Facestock

A premium matte litho stock with excellent ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face comes with a brightness of 84% and an opacity of 93%.

Type

Paper

Tear MD

50 Grams

Tear CD

55 Grams

Properties	Value	
Basis Weight	60lbs/3300 sq ft	
Caliper	3.90 Mil	
Opacity	93	
Brightness	84	

Regulatory Approval

RoHS

Yes

TPCH

Yes

Prop65

Yes

CPSIA

Yes

REACH

Yes

FSC

No

*Please contact your sales representative for details

<div><div>Adhesive</div><div>A general purpose, removable rubber based emulsion adhesive featuring good initial tack and moderate adhesion. It has limited plasticizer, UV and solvent resistance. This is a standard removable adhesive for tape reels, computer disks and kids stickers.</div></div>								
<div><div><div>Type</div><div>Removable</div></div><div><div>Composition</div><div>Latex</div></div><div><div>Shear</div><div>40</div></div></div>								
<div><div><div>Min. Application Temperature</div><div>40 F</div></div><div><div>Min. Service Temperature</div><div>1 F</div></div><div><div>Max. Application Temperature</div><div>120 F</div></div></div>								
<table><tr><th>Properties</th><th colspan="2">Value</th></tr><tr><td>Stainless Steel</td><td colspan="2">2.5 lbs/linear in.</td></tr></table>			Properties	Value		Stainless Steel	2.5 lbs/linear in.	
Properties	Value							
Stainless Steel	2.5 lbs/linear in.							

Glass	0,9lbs/linear in.
Polyethylene	1,8
Corrugated	1.00 lbs./in.
Painted Metal	1.6 lbs/linear in.
Loop Tack	1.50 oz/in²

Regulatory Approval		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	Direct Food No
Indirect Food Yes		

*Please contact your sales representative for details

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type

5517342

Tensile MD

34

Tear MD

32

Tensile CD

22

Tear CD

34

Description

Value

Basis Weight

40

Caliper

2.5

Regulatory Approval

RoHS

Yes

TPCH

Yes

Direct Food

No

Prop65

Yes

CPSIA

Yes

REACH

Yes

UL

No

*Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426

[800-358-4448](tel:800-358-4448)

orders.us@beontag.com