

Pressure-sensitive adhesives

Acrylic

Paper

60# ULTRA WHITE SemiGloss / TS700A / 40#SCK L-3

ITEM #79623

Facestock

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% Brightness and an 88% opacity.

Type

Paper

Tensile MD

35 Lbs/in

19 Lbs/in

Tear MD

47 Grams

46 Grams

Properties	Value
Basis Weight	60 # Rm 25 x 38
Caliper	3.20 Mil
Opacity	88
Brightness	90

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	FSC
Yes	Yes	No

^{*}Please contact your sales representative for details

Adhesive

A synthetic acrylic adhesive that has good long term removability from a wide variety of plastic surfaces. It also displays excellent die-cutting and stripping characteristics.

Type Removable	Composition Acrylic	Shear 0
Min. Application Temperature	Min. Service Temperature	Max. Application Temperature
40 F	-65 F	200 F

Properties	Value	
Glass	0lbs/linear in.	
Polyethylene	6,5lbs/linear in.	
Painted Metal	1.5 lbs/linear in.	
Regulatory Approval		
RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	Direct Food
Yes	Yes	No
Indirect Food		
Ves		

Yes

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

operations including die-cutting, butt cutting, line scoring and dispensing.				
Type 5517342				
Tensile MD	Tensile CD			
34	22			
Tear MD	Tear CD			
32	34			
Description	Value			
Basis Weight	40			
Caliper	2.5			
Regulatory Approval				
RoHS	Prop65	REACH		
Yes	Yes	Yes		

Yes

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

No

Yes

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com