

Pressure-sensitive adhesives

Latex

Paper

7 MIL C1S THERMAL TRANSFER / AP151 @ 1.5 CWT / 40#SCK

ITEM #854892

Facestock			
Type Paper			
Tensile MD 60 Lbs/in	Tensile CD 32 Lbs/in		
Tear MD 150 Grams	Tear CD 160 Grams		
Properties	Value		
Basis Weight	119lbs/3300 sq ft		
Caliper	6.90 Mil		
Brightness	88		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
TPCH	CPSIA	FSC	
Yes	Yes	No	

Adhesive

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Type Permanent	Composition Latex
Properties	Value
Glass	5.7 lbs/linear in.
Polyethylene	6,5

Regulatory Approval

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре

5517342

Tensile MD Tensile CD

34 22

Tear MD Tear CD 32 34

Description	Value
Basis Weight	40
Caliper	2.5

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	UL
Yes	Yes	No

Direct Food

No

Last update: 08/21/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

800-358-4448 orders.us@beontag.com