

Pressure-sensitive adhesives

Acrylic

Paper

#8 ESTATE WHITE VELLUM / TS585WS@ 1.6 Cwt. / 1.2 MIL PET L-3

ITEM #87666

FACESTOCK

Estate label is an uncoated, wet strength grade, face stock which meets the demanding packaging needs of the wine industry. The estate label combines prestige appearance with sophisticated production properties that ensure smooth performance on many high speed presses.

Type Paper

 Tensile MD
 Tensile CD

 30 Lbs/in
 16 Lbs/in

 Tear MD
 Tear CD

 50
 55

PROPERTIES VALUE

Basis Weight 60 # Rm 25 x 38

Caliper 5.30 Mil

Opacity 93

REGULATORY APPROVAL

RoHS
YesProp65
YesREACH
YesTPCH
YesCPSIA
YesUL
No

FSC No

ADHESIVE

A specialty adhesive designed to adhere to slightly wet surfaces with good ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for hard to label substrates.

_	2 '''	
Туре	Composition	Shear
Permanent	Acrylic	65

Min. Application Temperature Min. Service Temperature Max. Application Temperature

-20 F	-65 F	140 F	
PROPERTIES	VALUE		
Stainless Steel	4.8 lbs/linear in.		
Glass	3,2lbs/linear in.		
Polyethylene	6,5lbs/linear in.		

^{*}Please contact your sales representative for details

Corrugated 1.45 lbs./in.

Painted Metal 4.4 lbs/linear in.

Loop Tack 2.70 oz/in²

REGULATORY APPROVAL

RoHS Prop65 **REACH** Yes Yes Yes

CPSIA TPCH Direct Food

Yes Yes No

Indirect Food

Yes

*Please contact your sales representative for details

LINER

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Tensile MD Tensile CD

30000

Tear MD **Tear CD** 0 0

DESCRIPTION VALUE

Basis Weight 0

Caliper 1.2

REGULATORY APPROVAL

Prop65 **REACH RoHS** Yes Yes Yes

TPCH CPSIA Yes Yes

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com