

Pressure-sensitive adhesives

Acrylic

Paper

8 PT TAG / TR1 @ 1.0 Cwt. / 40#SCK L-10

ITEM #2962

Facestock

A coated 1 side tag stock with exceptionally high internal strength. It also offers high stiffness to withstand most conventional processing conditions such as die-cutting, perforating, fan-folding, and refolding operations

Type

Paper

Tensile MD Tensile CD

70 32

Tear MD130
Tear CD
130

Properties Value

Basis Weight 100

Caliper 8 mil

Regulatory Approval

RoHSProp65REACHYesYesYes
TPCH
CPSIA
Yes
No

FSC

No

*Please contact your sales representative for details

Adhesive

A specialty acrylic adhesive designed for clean removability from plastics and painted metal. Not recommended for curved or textured surfaces.

Туре	Composition	Shear
Removable	Acrylic	35
Min. Application Temperature	Min. Service Temperature	Max. Application Temperature
min Apphoacton Tomporataro	mini cor vico romporataro	max. Application femperature

Properties	Value

Stainless Steel 1.8 lbs/linear in.

Glass 0lbs/linear in.

Corrugated 0.55 lbs./in.

Painted Metal 1.3 lbs/linear in.

Loop Tack 1.35 oz/in²

Regulatory Approval

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type

17142

Tensile MD Tensile CD

34 22

Tear MD32

Tear CD
34

DescriptionValueBasis Weight40Caliper2.5

Regulatory Approval

RoHSProp65REACHYesYesYes
TPCH
CPSIA
Yes
No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com