

Pressure-sensitive adhesives

Acrylic Paper

## 8.5" X 11" RED FLUORESCENT / PERMANENT / 80# SCOREBACK L-3

ITEM #SC-016

## Facestock

A premium coated one side face stock in a bright fluorescent color with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting while maintaining consistency of color.

<b>Type</b> Paper		
Tensile MD	Tensile CD	
55 Lbs/in	13 Lbs/in	
Tear MD	Tear CD	
45 Grams	53 Grams	
Properties	Value	
Basis Weight	60 # Rm 25 x 38	
Caliper	3.80 Mil	
Regulatory Approval		
RoHS	Prop65	REACH
Yes	Yes	Yes
трсн	CPSIA	FSC
Yes	Yes	No
*Please contact your sales representative for	details	

**Adhesive** 

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

<b>Type</b> Permanent	<b>Composition</b> Acrylic
Properties	Value
Glass	2.8 lbs/linear in.
Polyethylene	1.5

<b>Regulatory Appro</b>	oval	
-------------------------	------	--

<b>RoHS</b>	<b>Prop65</b>	<b>REACH</b>	
Yes	Yes	Yes	
<b>TPCH</b>	<b>CPSIA</b>	<b>Direct Food</b>	
Yes	Yes	Yes	
<b>Indirect Food</b> Yes			
*Please contact your sales representative for details			

## Liner

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

<b>Type</b> 9019084			
<b>Tensile MD</b> 36	<b>Tensile CD</b> 21		
<b>Tear MD</b> 61	<b>Tear CD</b> 71		
Description	Value		
Basis Weight	72		
Caliper	4.6		
<b>Regulatory Approval</b>			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
<b>TPCH</b> Yes	<b>CPSIA</b> Yes	<b>UL</b> No	
162	ies	INO	

## Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com