

Pressure-sensitive adhesives

Latex Paper

# CHARTREUSE FLUORESCENT / TR447 @ 1.4 Cwt. / 40#SCK L-3

ITEM #707

#### Facestock

A premium coated one side face stock in a bright fluorescent color with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting.

Туре			
Paper			
Tensile MD	Tensile CD		
26 Lbs/in	14 Lbs/in		
Tear MD	Tear CD		
45 Grams	53 Grams		
Properties	Value		
Basis Weight	54 # Rm 25 x 38		
Caliper	3.80 Mil		
Opacity	0		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	

### Adhesive

A general purpose, removable rubber based emulsion adhesive featuring good initial tack and moderate adhesion. It has limited plasticizer, UV and solvent resistance. This is a standard removable adhesive for tape reels, computer disks and kids stickers.

<b>Type</b>	<b>Composition</b>	<b>Shear</b>
Removable	Latex	40
<b>Min. Application Temperature</b>	<b>Min. Service Temperature</b>	Max. Application Temperature
40 F	1 F	120 F
Properties	Value	

Stainless Steel	2.5 lbs/linear in.
Glass	0,9lbs/linear in.
Polyethylene	1,8
Corrugated	1.00 lbs./in.
Painted Metal	1.6 lbs/linear in.
Loop Tack	1.50 oz/in²
Regulatory Approval	

RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	Direct Food
Yes	Yes	No
Indirect Food		
Yes		
*Please contact your sales representative for	details	

#### Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

<b>Type</b> 5517342		
<b>Tensile MD</b> 34	<b>Tensile CD</b> 22	
<b>Tear MD</b> 32	<b>Tear CD</b> 34	
Description	Value	
Basis Weight	40	
Caliper	2.5	

## **Regulatory Approval**

RoHS	<b>Prop65</b> Yes	<b>REACH</b> Yes
Yes		
ТРСН	CPSIA	UL
Yes	Yes	No
Direct Food		

#### No

\*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag

6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> orders.us@beontag.com