

Pressure-sensitive adhesives

Acrylic Paper

DULL GOLD LAMINATED FOIL / AT333 @ 1.3 Cwt. / 40#SCK L-3

ITEM #980

Facestock A 60# acrylic topcoated foil paper that accepts water base and solvent base inks and can be embossed.

Туре			
Paper			
Tensile MD	Tensile CD		
36 Lbs/in	23 Lbs/in		
Tear MD	Tear CD		
50 Grams	51 Grams		
Properties	Value		
Basis Weight	60 # Rm 25 x 38		
Caliper	3.60 Mil		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	
*Please contact your sales repr	esentative for details		

Adhesive

An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Very good plasticizer, UV and solvent resistance. AT333 adhesive allows for short term

reposition on many substrates, yet displays excellent permanency at room temps.

Type	Composition	Shear
Permanent	Acrylic	60
Min. Application Temperature	Min. Service Temperature	Max. Application Temperature
-20 F	-65 F	160 F
Properties	Value	
Stainless Steel	4.7 lbs/linear in.	

Glass	1,3lbs/linear in.
Polyethylene	2.2
Corrugated	1.40 lbs./in.
Painted Metal	4.4 lbs/linear in.
Loop Tack	2.20 oz/in ²

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	Direct Food
Yes	Yes	No
Indirect Food		
Yes		
*Please contact your sales representative for	r details	

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type 5517342			
Tensile MD	Tensile CD		
34	22		
Tear MD	Tear CD		
32	34		
Description	Value		
Basis Weight	40		
Caliper	2.5		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
Direct Food			

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag

6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> orders.us@beontag.com