

Pressure-sensitive adhesives

Acrylic Film

# STARDUST HOLOGRAM TS523 50#SCK

ITEM #7451

#### Facestock

This versatile top coating is compatible with solvent base, water base and UV curable inks, as well as silk screen, flexographic and offset/letterpress printing.

<b>Type</b> Film		
<b>Tensile MD</b> 64 Lbs/in	<b>Tensile CD</b> 42 Lbs/in	
<b>Tear MD</b> 1400 Grams		
Elong MD 300	<b>Elong CD</b> 110	
Properties	Value	
Caliper	2.00 Mil	
Regulatory Approval		
RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	FSC
Yes	Yes	No
*Please contact your sales representative fo	r details	

#### Adhesive

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

<b>Type</b>	<b>Composition</b>	<b>Shear</b>
Permanent	Acrylic	350
<b>Min. Application Temperature</b>	<b>Min. Service Temperature</b>	<b>Max. Application Temperature</b>
35 F	-65 F	200 F
Properties	Value	
Stainless Steel	5.6 lbs/linear in.	

Glass	2,8lbs/linear in.
Polyethylene	2.9
Corrugated	1.50 lbs./in.
Painted Metal	4.9 lbs/linear in.
Loop Tack	2.70 oz/in <sup>2</sup>

## **Regulatory Approval**

RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	Direct Food
Yes	Yes	No
Indirect Food		
Yes		
*Please contact your sales representative for	details	

### Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

<b>Type</b> 5517353			
Tensile MD	Tensile CD		
40	24		
Tear MD	Tear CD		
44	48		
Description	Value		
Basis Weight	50		
Caliper	3.2		
<b>Regulatory Approval</b>			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
Direct Food			

Last update: 10/21/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426

800-358-4448 orders.us@beontag.com