

Pressure-sensitive adhesives

Acrylic

Paper

# TECHNI-GLOSS II HIGH GLOSS / IP400 / 1.2 MIL PET L-3

ITEM #88453

#### **Facestock**

A premium cast coated C1S white high gloss paper with a smooth print surface that offers excellent receptivity and print characteristics. The 90% gloss rating provides for the desired wet look label graphics that product manufacturers desire to enhance sales activity.

## Type

Paper

Tensile MD
25 Lbs/in
0 Lbs/in

Tear MD
35 Grams
40 Grams

Properties	Value
Basis Weight	57 # Rm 24 x 26
Caliper	3.70 Mil
Opacity	90
Brightness	87

### **Regulatory Approval**

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	UL
Yes	Yes	No

FSC No

#### **Adhesive**

A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.

Туре	Composition	Shear
Permanent	Acrylic	80

Min. Application Temperature Min. Service Temperature Max. Application Temperature

<sup>\*</sup>Please contact your sales representative for details

35 F	-65 F	200 F	
Properties	Value		
Stainless Steel	5.5 lbs/linear in.		
Glass	3,2lbs/linear in.		
Polyethylene	2		
Corrugated	1.45 lbs./in.		
Painted Metal	3.0 lbs/linear in.		
Loop Tack	5.00 oz/in²		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	Direct Food	
Yes	Yes	No	
Indirect Food			
Yes			
*Please contact your sales repres	entative for details		

•	
100	-
ıne	

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Tensile MD	Tensile CD		
30000	0		
Tear MD	Tear CD		
0	0		
Description	Value		
Basis Weight	0		
Caliper	1,2		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
TROU	CPSIA		
TPCH			

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com