



Pressure-sensitive adhesives

Acrylic

Paper

# TECHNI-GLOSS II / TS523 @ 1.5 Cwt. / 8 PT TAG L-3

ITEM #82052

### Facestock

A premium cast coated C1S white high gloss paper with a smooth print surface that offers excellent receptivity and print characteristics. The 90% gloss rating provides for the desired wet look label graphics that product manufacturers desire to enhance sales activity.

#### Type

Paper

#### Tensile MD

25 Lbs/in

#### Tensile CD

0 Lbs/in

#### Tear MD

35 Grams

#### Tear CD

40 Grams

| Properties   | Value           |
|--------------|-----------------|
| Basis Weight | 57 # Rm 24 x 26 |
| Caliper      | 3.70 Mil        |
| Opacity      | 90              |
| Brightness   | 87              |

### Regulatory Approval

|      |        |       |
|------|--------|-------|
| RoHS | Prop65 | REACH |
| Yes  | Yes    | Yes   |
| TPCH | CPSIA  | UL    |
| Yes  | Yes    | No    |
| FSC  |        |       |
| No   |        |       |

\*Please contact your sales representative for details

### Adhesive

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

|                              |                          |                              |
|------------------------------|--------------------------|------------------------------|
| Type                         | Composition              | Shear                        |
| Permanent                    | Acrylic                  | 350                          |
| Min. Application Temperature | Min. Service Temperature | Max. Application Temperature |

|   |                    |             |
|---|--------------------|-------------|
| 35 F  | -65 F              | 200 F       |
|   |                    |             |
| Properties  | Value              |             |
| Stainless Steel                                       | 5.6 lbs/linear in. |             |
| Glass   | 2,8lbs/linear in.  |             |
| Polyethylene  | 2.9                |             |
| Corrugated  | 1.50 lbs./in.      |             |
| Painted Metal   | 4.9 lbs/linear in. |             |
| Loop Tack   | 2.70 oz/in²        |             |
|   |                    |             |
| Regulatory Approval                                   |                    |             |
| RoHS  | Prop65             | REACH       |
| Yes   | Yes                | Yes         |
| TPCH  | CPSIA              | Direct Food |
| Yes   | Yes                | No          |
| Indirect Food   |                    |             |
| Yes   |                    |             |
| *Please contact your sales representative for details |                    |             |

Liner

An 8pt, 100# tag liner which has been silicone coated one side to give a controlled release. It has exceptionally high internal strength to withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes.

Type

17380

Tensile MD

63

Tensile CD

34

Tear MD

149

Tear CD

156

Description

Value

Basis Weight

102

Caliper

8

Regulatory Approval

RoHS

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

UL

No

Direct Food

No

\*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag  
6206 Wolf Creek Pike  
Trotwood, OH 45426

[800-358-4448](tel:800-358-4448)

[orders.us@beontag.com](mailto:orders.us@beontag.com)