

Pressure-sensitive adhesives

Acrylic

# TECHNI-THERM TR440 40# SCK L-3 TU

ITEM #873026

#### **Adhesive**

A specialty clear acrylic adhesive showing good initial removable tack with high shear and high removable adhesion. This adhesive has excellent clarity & minimum cold flow. Good removability on a wide range of substrates including corrugated and many plastic surfaces.

Composition Shear **Type** Removable 110 Acrylic

Min. Application Temperature **Min. Service Temperature** Max. Application Temperature

40 F -65 F 150 F

**Properties** Value Stainless Steel 4.7 lbs/linear in. 3lbs/linear in. **Glass Polyethylene** 1.4

Corrugated

**Painted Metal** 4.2 lbs/linear in.

**Loop Tack** 1.70 oz/in<sup>2</sup>

### **Regulatory Approval**

**RoHS** Prop65 **REACH** Yes Yes Yes

Yes

**TPCH CPSIA Direct Food** 

1.20 lbs./in.

**Indirect Food** 

Yes

Yes

\*Please contact your sales representative for details

## Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. Technicote Ultimate silicone release coating provides consistent stripping at high converting speeds through a flat release profile. This paper has a smooth, caliper consistent surface and withstands all conventional processing operations.

No

#### **Type**

718322

**Tensile MD Tensile CD** 

30	20		
Tear MD	Tear CD		
32	34		
Description	Value		
Basis Weight	40		
Caliper	2.5		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
Direct Food			
No			
NO			

Last update: 08/19/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com