|| beontag

Pressure-sensitive adhesives

HDPE

10 mil High End Synthetic Paper

ITEM #80091

Facestock

A matte smooth white reinforced polyethylene film suitable for a wide range of applications where durability, strength, moisture, chemical resistance and superb printability (including flexo, litho, gravure, and thermal transfer) are required.

| Type HDPE | | |
|---|---------------------------|-------|
| Tensile MD 4500 | Tensile CD 4200 | |
| Tear MD 280 | Tear CD 1450 | |
| Elong MD 120 | Elong CD 120 | |
| Properties | Value | |
| Caliper | 10 mil | |
| Regulatory Approval | | |
| RoHS | Prop65 | REACH |
| Yes | Yes | Yes |
| ТРСН | CPSIA | FSC |
| Yes | Yes | No |
| *Please contact your sales representative for details | | |

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> orders.us@beontag.com