

Pressure-sensitive adhesives

Acrylic Paper

## 10 PT C1S TAG / TR1 @ 1.0 Cwt. / 40#SCK L-3

ITEM #99945

## Facestock

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers excellent stiffness and high internal strength.

<b>Type</b> Paper		
<b>Tear MD</b> 205 Grams	<b>Tear CD</b> 200 Grams	
Properties	Value	
Caliper	10.00 Mil	
Brightness	94	
Regulatory Approval		
RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	UL
Yes	Yes	No
FSC		
No		
*Please contact your sales representative for	details	

## **Adhesive**

A specialty acrylic adhesive designed for clean removability from plastics and painted metal. Not recommended for curved or textured surfaces.

<b>Type</b> Removable	<b>Composition</b> Acrylic	<b>Shear</b> 35
<b>Application Temperature</b> 40 F	<b>Min. Application Temperature</b> -65 F	Max. Application Temperature 120 F
Properties	Value	
•	Value	
Stainless Steel	1.8 lbs/linear in.	

Polyethylene	0.0		
Corrugated	0.55 lbs./in.		
Painted Metal	1.2 lbs/linear in.		
Loop Tack	1.35 lbs./in.		
Regulatory Approval			
RoHS	Prop65	REACH	
<b>RoHS</b> Yes	<b>Prop65</b> Yes	<b>REACH</b> Yes	
	-		
Yes	Yes	Yes	
Yes TPCH	Yes	Yes UL	
Yes <b>TPCH</b> Yes	Yes CPSIA Yes	Yes UL	

## Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

<b>Type</b> 5517342			
Tensile MD	Tensile CD		
34 Lbs/In	22 Lbs/In		
Tear MD	Tear CD		
32 Grams	34 Grams		
Description	Value		
Basis Weight	40 Lbs/Rm		
Caliper	2.5 Mil		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	

ТРСН	CPSIA	UL	
Yes	Yes	No	
<b>Direct Food</b> No			
*Please contact your sales repre	sentative for details		

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>