

Pressure-sensitive adhesives

Acrylic Paper

## 100# UNCOATED TAG / TR440 @ 1.0 Cwt. / 3.4 MIL LAYFLAT L-5

## ITEM #92377

Facestock			
An uncoated tag stock the	at has a smooth consistent surface for	ease in printing.	
Туре			
Paper			
Tear MD	Tear CD		
135 Grams	150 Grams		
Properties	Value		
Caliper	7.50 Mil		
Brightness	84		
<b>Regulatory Approval</b>			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	
*Please contact your sales rep	presentative for details		

## **Adhesive**

A specialty clear acrylic adhesive showing good initial removable tack with high shear and high removable adhesion. This adhesive has excellent clarity & minimum cold flow. Good removability on a wide range of substrates including corrugated and many plastic surfaces.

<b>Composition</b> Acrylic	<b>Type</b> Removable	<b>Shear</b> 110
<b>Application Temperature</b> 40 F	<b>Min. Application Temperature</b> -65 F	Max. Application Temperature 150 F
Properties	Value	
Stainless Steel	4.7 lbs/linear in.	
Glass	3.0	
Polyethylene	1.4	

Corrugated	1.20 lbs./in.		
Painted Metal	4.2 lbs/linear in.		
Loop Tack	1.70 lbs./in.		
<b>Regulatory Approval</b>			
RoHS	Prop65	REACH	
Yes	No	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
Direct Food	Indirect Food		
No	Yes		
*Please contact your sales represe	entative for details		

## Liner

A bleached kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand die-cutting, marginal punching, perforating, fanfolding and refolding process while providing excellent dimensional stability.

Tensile MD	Tensile CD		
35	15		
Tear MD	Tear CD		
50	75		
Description	Value		
Basis Weight	0		
Caliper	3,4		
canper	0,1		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA		
Yes	Yes		

\*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 222 Mound Avenue Miamisburg, OH 45342 800-358-4448 orders.us@beontag.com