

Pressure-sensitive adhesives

Acrylic

Paper

# 17.25" X 22.25" PREMIUM UNCOATED OFFSET / PERMA-NENT / 80# SCOREBACK L-3

ITEM #SC-008

#### **Facestock**

This premium uncoated facestock features a 98% brightness, balanced white shade, superior opacity, and a smooth velvety feel.

#### **Type**

Paper

Properties	Value
Caliper	4.6 mil

# **Regulatory Approval**

Yes	Yes	Yes
TPCH	CPSIA	<b>UL</b>
Yes	Yes	No

FSC No

## **Adhesive**

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

<b>Composition</b> Acrylic	<b>Type</b> Permanent	Shear 300
<b>Application Temperature</b> 35 F	<b>Min. Application Temperature</b> -65 F	<b>Max. Application Temperature</b> 180 F
Properties	Value	
Stainless Steel	5.2 lbs/linear in.	
Glass	2.8	
Polyethylene	2.9	

<sup>\*</sup>Please contact your sales representative for details

Corrugated 1.40 lbs./in.

Painted Metal 5.2 lbs/linear in.

Loop Tack 2.20 lbs./in2

#### **Regulatory Approval**

RoHSProp65REACHYesNoYes

TPCHCPSIAULYesYesNo

Direct Food Indirect Food

Yes Yes

#### Liner

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

#### **Type**

9019084

Tensile MD

36 Lbs/ln

21 Lbs/ln

Tear MD

61 Grams

Tensile CD

71 Grams

Description	Value
Basis Weight	72 Lbs/Rm

Caliper 4.6 Mil

## **Regulatory Approval**

RoHS
Yes
Yes
Yes

CPSIA
Yes
No

#### Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

<sup>\*</sup>Please contact your sales representative for details

<sup>\*</sup>Please contact your sales representative for details

ADDRESS:
Beontag
222 Mound Avenue Miamisburg, OH 45342
800-358-4448
orders.us@beontag.com