

2 MIL CLEAR ACETATE / AP151 HCWT / 65#FBK L-3

ITEM #951771

| | | |
|---|--------------------------------|---------------------|
| Facestock A 2 mil clear film with excellent ink receptivity and printability. | | |
| Type Film | | |
| Tensile MD 10000 Psi | Tensile CD 10000 Psi | |
| Elong MD 325 | | |
| | | |
| Properties | Value | |
| Caliper | 2.00 Mil | |
| | | |
| Regulatory Approval | | |
| RoHS Yes | Prop65 Yes | REACH Yes |
| TPCH Yes | CPSIA Yes | FSC No |
| *Please contact your sales representative for details | | |

| | | |
|--|--|--|
| Adhesive An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits. | | |
| Composition Hot Melt | Type Permanent | Shear 80 |
| Application Temperature 35 F | Min. Application Temperature -65 F | Max. Application Temperature 220 F |
| Properties | Value | |
| Stainless Steel | 7.3 lbs/linear in. | |
| Glass | 5.7 | |
| Polyethylene | 6.5 | |

| | | |
|---|-----------------------------|---------------------|
| Corrugated | 2.50 lbs./in. | |
| Painted Metal | 7.0 lbs/linear in. | |
| Loop Tack | 5.00 lbs./in ² | |
| <hr/> | | |
| Regulatory Approval | | |
| RoHS Yes | Prop65 No | REACH Yes |
| TPCH Yes | CPSIA Yes | UL No |
| Direct Food No | Indirect Food Yes | |
| *Please contact your sales representative for details | | |

Liner

A fully bleached kraft liner which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes.

Type

17365

Tensile MD

33 Lbs/In

Tensile CD

18 Lbs/In

Tear MD

51 Grams

Tear CD

53 Grams

Description

Value

Basis Weight

65 Lbs/Rm

Caliper

3.8 Mil

Regulatory Approval

RoHS

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

UL

No

Direct Food

No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages. BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at

BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

[800-358-4448](tel:800-358-4448)

orders.us@beontag.com