

Pressure-sensitive adhesives

Acrylic

Paper

26" X 24" PREMIUM UNCOATED OFFSET / PERMANENT / 80# SCOREBACK L-3

ITEM #SC-309

Facestock

A premium 98 Bright White offset sheet that is excellent for all high end offset printing.

Type

Paper

Properties	Value
Caliper	4.20 Mil
Opacity	94
Brightness	98

Regulatory Approval

Prop65	REACH
Yes	Yes
CPSIA	FSC
Vac	No
	•

^{*}Please contact your sales representative for details

Adhesive

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Composition Acrylic	Type Permanent	Shear 300
Application Temperature 35 F	Min. Application Temperature -65 F	Max. Application Temperature 180 F
Properties	Value	
Stainless Steel	5.2 lbs/linear in.	
Glass	2.8	
Polyethylene	2.9	

Corrugated 1.40 lbs./in.

Painted Metal 5.2 lbs/linear in.

Loop Tack 2.20 lbs./in2

Regulatory Approval

RoHSProp65REACHYesNoYes

TPCHCPSIAULYesYesNo

Direct Food Indirect Food

Yes Yes

Liner

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

Type

9019084

Tensile MD

36 Lbs/ln

21 Lbs/ln

Tear MD

61 Grams

Tensile CD

71 Grams

Description	Value
Basis Weight	72 Lbs/Rm

Caliper 4.6 Mil

Regulatory Approval

RoHS
Yes
Yes
Yes

CPSIA
Yes
No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

ADDRESS:
Beontag
222 Mound Avenue Miamisburg, OH 45342
800-358-4448
orders.us@beontag.com