

Pressure-sensitive adhesives

Acrylic

Paper

#4 ESTATE WHITE / TS585WS @ 1.6 Cwt. / 1.2 MIL PET L-3

ITEM #87665

Facestock

Estate label is an uncoated face stock, wet strength grade, which meets the demanding packaging needs of the wine industry. The estate label combines prestige appearance with sophisticated production properties that ensure smooth performance on many high speed presses.

Type

Paper

Properties	Value
Caliper	5.50 Mil
Opacity	93
Brightness	87

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	UL
Yes	Yes	No

FSC No

Adhesive

A specialty adhesive designed to adhere to slightly wet surfaces with good ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for hard to label substrates.

Composition Acrylic	Type Permanent	Shear 65
Application Temperature -20 F	Min. Application Temperature -65 F	Max. Application Temperature 140 F
Properties	Value	
Stainless Steel	4.8 lbs/linear in.	

^{*}Please contact your sales representative for details

Glass 3.2

Polyethylene 2.0

Corrugated 1.45 lbs./in.

Painted Metal 4.4 lbs/linear in.

Loop Tack 2.70 lbs./in.

Regulatory Approval

RoHSProp65REACHYesNoYesTPCHCPSIAULYesYesNo

Direct Food Indirect Food

No Yes

*Please contact your sales representative for details

Liner

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Tensile MD Tensile CD

30000

Tear MD Tear CD

0 0

Description Value

Caliper 1,2

Regulatory Approval

Basis Weight

RoHSProp65REACHYesYesYes

0

TPCH CPSIA
Yes Yes

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag
222 Mound Avenue Miamisburg, OH 45342
800-358-4448
orders.us@beontag.com