

Pressure-sensitive adhesives

Acrylic

Paper

#4 ESTATE WHITE / TS585WS / 44#PK L-3

ITEM #5790

Facestock

Estate label is an uncoated face stock, wet strength grade, which meets the demanding packaging needs of the wine industry. The estate label combines prestige appearance with sophisticated production properties that ensure smooth performance on many high speed presses.

Type

Paper

Properties	Value
Caliper	5.50 Mil
Opacity	93

Regulatory Approval

RoHS

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

UL

No

FSC

No

*Please contact your sales representative for details

Adhesive

A specialty adhesive designed to adhere to slightly wet surfaces with good ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for hard to label substrates.

Composition	Type	Shear
Acrylic	Permanent	65
Application Temperature	Min. Application Temperature	Max. Application Temperature
-20 F	-65 F	140 F

Typical Adhesion values

Properties	Value
Stainless Steel	4.8 lbs/linear in.
Glass	3.0

Polyethylene	2.0
Corrugated	1.45 lbs./in.
Painted Metal	4.4 lbs/linear in.
Loop Tack	2.70 lbs./in.

Regulatory Approval

RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	Direct Food No
Indirect Food Yes		

*Please contact your sales representative for details

Liner

A medium weight natural kraft coated 1 side (C1S) with a gloss polyethylene. Silicone coating has been added on the gloss side (C1S) for a controlled release. It has superb smoothness, excellent dimensional stability and exceptional layflat characteristics.

Type
17745

Tensile MD 35 Lbs/In	Tensile CD 13 Lbs/In
Tear MD 35 Grams	Tensile CD 50 Grams

Description	Value
Basis Weight	44 Lbs/Rm
Caliper	3.2 Mil

Regulatory Approval

RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No		

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

[800-358-4448](tel:800-358-4448)

orders.us@beontag.com