

Pressure-sensitive adhesives

Acrylic

Paper

#55 HIBRIGHT SEMIGLOSS / TR440 @ 1.0 Cwt. / 40#SCK L-3

ITEM #88031

Facestock

A premium semigloss calendar coated one side stock with excellent ink receptivity and print characteristics. This stock offers an 88% brightness has an 87% opacity and a 70% gloss rating.

Type

Paper

Tensile MD

35 Lbs/in

Tear MD

Tear CD

35 Grams

Tear CD

Properties Value

Caliper 2.80 Mil

Opacity 87

Regulatory Approval

Brightness

RoHSProp65REACHYesYesYes
TPCH
Yes
Yes
No

88

*Please contact your sales representative for details

Adhesive

A specialty clear acrylic adhesive showing good initial removable tack with high shear and high removable adhesion. This adhesive has excellent clarity & minimum cold flow. Good removability on a wide range of substrates including corrugated and many plastic surfaces.

Type Removable	Composition Acrylic	Shear 110
Application Temperature 40 F	Min. Application Temperature -65 F	Max. Application Temperature 150 F
Properties	Value	

Stainless Steel 4.7 lbs/linear in.

Glass 3.0

Polyethylene 1.4

Corrugated 1.20 lbs./in.

Painted Metal 4.2 lbs/linear in.

Loop Tack 1.70 lbs./in.

Regulatory Approval

RoHSProp65REACHYesNoYesTPCHCPSIAULYesYesNo

Direct Food Indirect Food

No Yes

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type

5517342

Tensile MDTensile CD34 Lbs/ln22 Lbs/ln

Tear MD32 Grams

Tear CD
34 Grams

Description Value

Basis Weight 40 Lbs/Rm

Caliper 2.5 Mil

Regulatory Approval

RoHS
YesProp65
YesREACH
YesTPCH
YesCPSIA
YesUL
No

Direct Food

No

Last update: 05/01/2024

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com