

Pressure-sensitive adhesives

Acrylic

Paper

#6 WHITE PEARLIZED ESTATE / IP400 @ 1.7 Cwt. / 1.2 MIL PET L-3

ITEM #78987

Facestock

This wet strength grade paper face stock features a pearlized white coating on the print side which provides a unique, attractive appearance on glass bottles. It is a favorite for wine and specialty beverage Products.

Type

Paper

| Properties | Value |
|------------|----------|
| Caliper | 5.50 Mil |
| Opacity | 94 |

Regulatory Approval

| RoHS | Prop65 | REACH |
|------|--------|-------|
| Yes | Yes | Yes |
| | | |
| TPCH | CPSIA | FSC |
| Yes | Yes | No |
| | | |

^{*}Please contact your sales representative for details

Adhesive

A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.

| Composition Acrylic | Type Permanent | Shear 78 |
|-------------------------------------|---|--|
| Application Temperature 35 F | Min. Application Temperature -65 F | Max. Application Temperature 200 F |
| Properties | Value | |
| Stainless Steel | 5.3 lbs/linear in. | |
| Glass | 3.2 | |
| Polyethylene | 2.0 | |
| Corrugated | 1.40 lbs./in. | |

Painted Metal 2.8 lbs/linear in.

Loop Tack 4.85 lbs./in.

Regulatory Approval

RoHSProp65REACHYesNoYes

TPCHCPSIAULYesYesNo

Direct Food Indirect Food

No Yes

Liner

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

0

Tensile MD Tensile CD

30000

Tear MD Tear CD

Description Value

Basis Weight 0

Caliper 1,2

Regulatory Approval

RoHSProp65REACHYesYesYes

TPCH
Yes

CPSIA
Yes

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

800-358-4448

orders.us@beontag.com

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details