



Pressure-sensitive adhesives

Acrylic

Paper

60# CLASSIC CREST SOLAR WHITE WS / TS585WS @ 1.6 Cwt./ 1.2 MIL PET L-3

ITEM #87737

Facestock

60# Fine Textured uncoated paper face sheet with internal wet strength properties. Most commonly used for wine label that is exposed to cold wet conditions.

Type

Paper

Tensile MD

9 Lbs/in

Tensile CD

6 Lbs/in

Tear MD

67 Grams

Tear CD

59 Grams

Properties	Value
Caliper	4.30 Mil
Opacity	90
Brightness	91

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	FSC
Yes	Yes	No

*Please contact your sales representative for details

Adhesive

A specialty adhesive designed to adhere to slightly wet surfaces with good ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for hard to label substrates.

Composition	Type	Shear
Acrylic	Permanent	65
Application Temperature	Min. Application Temperature	Max. Application Temperature
-20 F	-65 F	140 F

Properties	Value
------------	-------

Stainless Steel	4.8 lbs/linear in.
Glass	3.2
Polyethylene	2.0
Corrugated	1.45 lbs./in.
Painted Metal	4.4 lbs/linear in.
Loop Tack	2.70 lbs./in.

Regulatory Approval		
RoHS	Prop65	REACH
Yes	No	Yes
TPCH	CPSIA	UL
Yes	Yes	No
Direct Food	Indirect Food	
No	Yes	

*Please contact your sales representative for details

Liner

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Tensile MD	Tensile CD
30000	0
Tear MD	Tear CD
0	0

Description	Value
Basis Weight	0
Caliper	1,2

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	
Yes	Yes	

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages. BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

[800-358-4448](tel:800-358-4448)

orders.us@beontag.com