

Pressure-sensitive adhesives

Rubber

Paper

# 60# MATTE LITHO / TL250 @ 2.5 Cwt. / 40#SCK L-3

ITEM #8960

## Facestock

A premium matte litho stock with excellent ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face comes with a brightness of 84% and an opacity of 93%.

### Type

Paper

### Tear MD

50 Grams

### Tensile CD

55 Grams

### Properties

### Value

### Caliper

3.90 Mil

### Opacity

93

## Regulatory Approval

### RoHS

Yes

### Prop65

Yes

### REACH

Yes

### TPCH

Yes

### CPSIA

Yes

### FSC

No

\*Please contact your sales representative for details

## Adhesive

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

### Composition

Rubber

### Type

Permanent

## Typical Adhesion values

### Properties

### Value

### Glass

6.0

### Polyethylene

7.0

## Regulatory Approval

### RoHS

### Prop65

### REACH

Yes	Yes	Yes
<b>TPCH</b>	<b>CPSIA</b>	<b>UL</b>
Yes	Yes	No
<b>Direct Food</b>	<b>Indirect Food</b>	<b>FDA 21 CFR 175.105, BfR XIV</b>
No	Yes	No

\*Please contact your sales representative for details

## Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

### Type

5517342

### Tensile MD

34 Lbs/In

### Tensile CD

22 Lbs/In

### Tear MD

32 Grams

### Tensile CD

34 Grams

### Description

### Value

### Basis Weight

40 Lbs/Rm

### Caliper

2.5 Mil

## Regulatory Approval

### RoHS

Yes

### Prop65

Yes

### REACH

Yes

### TPCH

Yes

### CPSIA

Yes

### UL

No

### Direct Food

No

\*Please contact your sales representative for details

Last update: 05/01/2024

**WARRANTY:** All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

### ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

[800-358-4448](tel:800-358-4448)

[orders.us@beontag.com](mailto:orders.us@beontag.com)