

Pressure-sensitive adhesives

Hot Melt

Paper

60# MATTE LITHO / TR447 @ 1.4 Cwt. / 40#SCK L-3

ITEM #211

Facestock

A premium matte litho stock with excellent ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face comes with a brightness of 84% and an opacity of 93%.

	_		
Τ	v	p	e

Paper

Tear MDTear CD50 Grams55 Grams

Properties Value

Caliper 3.90 Mil

Opacity 93

Brightness 84

Regulatory Approval

RoHSProp65REACHYesYesYes
TPCH
CPSIA
FSC
Yes
No

Adhesive

A general purpose, removable rubber based emulsion adhesive featuring good initial tack and moderate adhesion. It has limited plasticizer, UV and solvent resistance. This is a standard removable adhesive for tape reels, computer disks and kids stickers.

Composition Hot Melt Application Temperature 40 F	Type Removable Min. Application Temperature 1 F	Shear 40 Max. Application Temperature 120 F
Properties	Value	
Stainless Steel	2.5 lbs/linear in.	

^{*}Please contact your sales representative for details

Polyethylene 1.8

Corrugated 1.00 lbs./in.

Painted Metal 1.6 lbs/linear in.

Loop Tack 1.50 lbs./in.

Regulatory Approval

RoHSProp65REACHYesNoYesTPCHCPSIAULYesYesNo

Direct Food Indirect Food

No Yes

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре

5517342

Tensile MDTensile CD34 Lbs/ln22 Lbs/ln

Tear MDTear CD32 Grams34 Grams

Description Value

Basis Weight 40 Lbs/Rm

Caliper 2.5 Mil

Regulatory Approval

RoHS
YesProp65
YesREACH
YesTPCH
YesCPSIA
YesUL
No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
222 Mound Avenue Miamisburg, OH 45342
800-358-4448
orders.us@beontag.com