

Pressure-sensitive adhesives

Acrylic Paper

60# ULTRA WHITE SemiGloss / TS700A / 40#SCK L-3



ITEM #79623

Facestock

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% Brightness and an 88% opacity.

Туре			
Paper			
Tensile MD	Tensile CD		
35 Lbs/in	19 Lbs/in		
Tear MD	Tear CD		
47 Grams	46 Grams		
Properties	Value		
Caliper	3.20 Mil		
Opacity	88		
Brightness	90		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	Yes	

Adhesive

A synthetic acrylic adhesive that has good long term removability from a wide variety of plastic surfaces. It also displays excellent die-cutting and stripping characteristics.

Composition	Type	Application Temperature	
Acrylic	Removable	40 F	
Min. Application Temperature	Max. Application Temperature		
-65 F	200 F		
Properties	Value		

Glass	0.0		
Polyethylene	0.0		
Painted Metal	1.5 lbs/linear in.		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	No	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
Direct Food	Indirect Food		
No	Yes		

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре

5517342

Tensile MD 34 Lbs/In	Tensile CD 22 Lbs/In	
Tear MD 32 Grams	Tear CD 34 Grams	
Description	Value	
Basis Weight	40 Lbs/Rm	
Caliper	2.5 Mil	
Regulatory Approval		
RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	UL
Yes	Yes	No

Direct Food

No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages. BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 222 Mound Avenue Miamisburg, OH 45342 <u>800-358-4448</u> <u>orders.us@beontag.com</u>