

#8 ESTATE WHITE VELLUM / IP400 @ 1.7 Cwt. / 1.2 MIL PET L-3

ITEM #80008

Facestock

Estate label is an uncoated, wet strength grade, face stock which meets the demanding packaging needs of the wine industry. The estate label combines prestige appearance with sophisticated production properties that ensure smooth performance on many high speed presses.

Type

Paper

Tensile MD

30 Lbs/in

Tensile CD

16 Lbs/in

Tear MD

50

Tear CD

55

Properties

Value

Caliper

5.30 Mil

Opacity

93

Regulatory Approval

RoHS

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

UL

No

FSC

No

*Please contact your sales representative for details

Adhesive

A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.

Composition

Acrylic

Type

Permanent

Shear

80

Application Temperature

35 F

Min. Application Temperature

-65 F

Max. Application Temperature

200 F

Properties	Value
Stainless Steel	5.5 lbs/linear in.
Glass	3.2
Polyethylene	2.0
Corrugated	1.45 lbs./in.
Painted Metal	3.0 lbs/linear in.
Loop Tack	5.00 lbs./in.

Regulatory Approval		
RoHS	Prop65	REACH
Yes	No	Yes
TPCH	CPSIA	UL
Yes	Yes	No
Direct Food	Indirect Food	
No	Yes	

*Please contact your sales representative for details

Liner

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

<div>Tensile MD</div> <div>30000</div>	<div>Tensile CD</div> <div>0</div>
<div>Tear MD</div> <div>0</div>	<div>Tear CD</div> <div>0</div>

Description	Value
Basis Weight	0
Caliper	1,2

Regulatory Approval

<div>RoHS</div> <div>Yes</div>	<div>Prop65</div> <div>Yes</div>	<div>REACH</div> <div>Yes</div>
<div>TPCH</div> <div>Yes</div>	<div>CPSIA</div> <div>Yes</div>	

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

[800-358-4448](tel:800-358-4448)

orders.us@beontag.com