

80# SemiGloss / AT333 @ 1.30 Cwt. / 40#SCK L-3

ITEM #88329

Facestock

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 89% brightness and an 92% opacity.

Type

Paper

Properties	Value
Caliper	4.20 Mil
Opacity	93
Brightness	83

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	FSC
Yes	Yes	No

*Please contact your sales representative for details

<div><div>Adhesive</div><div>An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Very good plasticizer, UV and solvent resistance. AT333 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps.</div></div>																	
<table><tr><td>Composition</td><td>Type</td><td>Shear</td></tr><tr><td>Acrylic</td><td>Permanent</td><td>60</td></tr><tr><td>Application Temperature</td><td>Min. Application Temperature</td><td>Max. Application Temperature</td></tr><tr><td>-20 F</td><td>-65 F</td><td>160 F</td></tr></table>			Composition	Type	Shear	Acrylic	Permanent	60	Application Temperature	Min. Application Temperature	Max. Application Temperature	-20 F	-65 F	160 F			
Composition	Type	Shear															
Acrylic	Permanent	60															
Application Temperature	Min. Application Temperature	Max. Application Temperature															
-20 F	-65 F	160 F															
<table><tr><th>Properties</th><th colspan="2">Value</th></tr><tr><td>Stainless Steel</td><td colspan="2">4.7 lbs/linear in.</td></tr><tr><td>Glass</td><td colspan="2">1.3</td></tr><tr><td>Polyethylene</td><td colspan="2">2.2</td></tr><tr><td>Corrugated</td><td colspan="2">1.40 lbs./in.</td></tr></table>			Properties	Value		Stainless Steel	4.7 lbs/linear in.		Glass	1.3		Polyethylene	2.2		Corrugated	1.40 lbs./in.	
Properties	Value																
Stainless Steel	4.7 lbs/linear in.																
Glass	1.3																
Polyethylene	2.2																
Corrugated	1.40 lbs./in.																

Painted Metal			4.4 lbs/linear in.
Loop Tack			2.20 lbs./in.
Regulatory Approval			
RoHS		Prop65	REACH
Yes		No	Yes
TPCH		CPSIA	UL
Yes		Yes	No
Direct Food		Indirect Food	
No		Yes	
*Please contact your sales representative for details			

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type

5517342

Tensile MD

34 Lbs/In

Tear MD

32 Grams

Tensile CD

22 Lbs/In

Tear CD

34 Grams

Description

Value

Basis Weight

40 Lbs/Rm

Caliper

2.5 Mil

Regulatory Approval

RoHS

Yes

TPCH

Yes

Direct Food

No

Prop65

Yes

CPSIA

Yes

REACH

Yes

UL

No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages. BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

[800-358-4448](tel:800-358-4448)

orders.us@beontag.com