

Pressure-sensitive adhesives

Acrylic

Acrylic

Paper

BRIGHT SILVER METALLIZED PAPER / TP170 @ 1.3 Cwt. / 40#SCK L-3

ITEM #688165

Facestock

A bright silver paper facestock. A reflective, acrylic lacquer coated metallized paper facestock for excellent flexographic print results.

Type

Paper

Properties	Value
Caliper	2.60 Mil

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	FSC
Yes	Yes	No

^{*}Please contact your sales representative for details

Adhesive

A general purpose acrylic adhesive showing good initial tack with high shear and high ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Composition Acrylic	Type Permanent	Shear 300	
Application Temperature 35 F	Min. Application Temperature -65 F	Max. Application Temperature 180 F	
Properties	Value		
Stainless Steel	5.2 lbs/linear in.		
Glass	3.2	3.2	
Polyethylene	1.6	1.6	
Corrugated	1.40 lbs./in.		
Painted Metal	5.2 lbs/linear		

Loop Tack 2.20	bs./in2
----------------	---------

Regulatory Approval

RoHS
YesProp65
NoREACH
YesTPCHCPSIAUL

Yes

Direct Food Indirect Food

No Yes

Adhesive

Yes

A general purpose patterned acrylic adhesive showing good initial tack with high shear and high ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

No

Composition Acrylic	Type Permanent	Shear 300
Application Temperature 35 F	Min. Application Temperature -65 F	Max. Application Temperature 180 F

Properties	Value
Stainless Steel	5.2 lbs/linear in.
Glass	3.2
Polyethylene	1.6
Corrugated	1.40 lbs./in.
Painted Metal	5.2 lbs/linear
Loop Tack	2.20 lbs./in2

Regulatory Approval

RoHS	Prop65	REACH
Yes	No	Yes
TPCH	CPSIA	UL
Yes	Yes	No
Direct Food No	Indirect Food Yes	

^{*}Please contact your sales representative for details

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

^{*}Please contact your sales representative for details

Туре
5517342

Tensile MDTensile CD34 Lbs/ln22 Lbs/ln

Tear MDTear CD32 Grams34 Grams

Description	Value
Basis Weight	40 Lbs/Rm
Caliper	2.5 Mil

Regulatory Approval

RoHS Yes	Prop65 Yes	REACH Yes
ТРСН	CPSIA	UL
Yes	Yes	No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

800 - 358 - 4448

orders.us@beontag.com

^{*}Please contact your sales representative for details