

Pressure-sensitive adhesives

Hot Melt Paper

DULL SILVER LAMINATED FOIL / AP151 @ 1.3 Cwt. / 40#SCK L-3

ITEM #151020

Facestock A 60# acrylic topcoated foil paper that accepts water base and solvent base inks and can be embossed.		
Tensile CD		
23 Lbs/in		
Tear CD		
51 Grams		
Value		
3.60 Mil		
Prop65	REACH	
Yes	Yes	
CPSIA	FSC	
Yes	No	
esentative for details		
	Tensile CD23 Lbs/in23 Lbs/inTear CD51 GramsValue3.60 MilProp65YesCPSIAYes	Tensile CD 23 Lbs/in Z3 Lbs/in Tear CD 51 Grams 51 Grams Value 3.60 Mil Prop65 REACH Yes Yes CPSIA FSC Yes No

Adhesive

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Composition Hot Melt	Type Permanent	Shear 80
Application Temperature 35 F	Min. Application Temperature -65 F	Max. Application Temperature 220 F
Properties	Value	
Properties Stainless Steel	Value 7.3 lbs/linear in.	

Polyethylene	6.5	
Corrugated	2.50 lbs./in.	
Painted Metal	7.0 lbs/linear in.	
Loop Tack	5.00 lbs./in.	
Regulatory Approval		
RoHS	Prop65	REACH
RoHS Yes	Ргор65 No	REACH Yes
	-	
Yes	No	Yes
Yes TPCH	No	Yes UL
Yes TPCH Yes	No CPSIA Yes	Yes UL

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре			
5517342			
Tensile MD	Tensile CD		
34 Lbs/In	22 Lbs/In		
Tear MD	Tear CD		
32 Grams	34 Grams		
Description	Value		
Basis Weight	40 Lbs/Rm		
Opliner	O E Mil		
Caliper	2.5 Mil		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	

IPCH	CPSIA	UL
Yes	Yes	No
Direct Food		
No		
	dataila	
*Please contact your sales representative for o	Jetalis	

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 222 Mound Avenue Miamisburg, OH 45342 <u>800-358-4448</u> orders.us@beontag.com