

Pressure-sensitive adhesives

Hot Melt

Paper

# DULL SILVER LAMINATED FOIL / TL250 @ 2.5 Cwt. / 3.4 MIL LAYFLAT L-3

ITEM #851916

#### **Facestock**

A 60# acrylic topcoated foil paper that accepts water base and solvent base inks and can be embossed.

# Туре

Paper

Tensile MD

36 Lbs/in

23 Lbs/in

Tear MD

Tear CD

50 Grams

51 Grams

Properties Value

Caliper 3.60 Mil

## **Regulatory Approval**

RoHSProp65REACHYesYesYes
TPCH
Yes
CPSIA
Yes
No

\*Please contact your sales representative for details

#### **Adhesive**

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

CompositionTypeShearHot MeltPermanent80

Application Temperature Min. Application Temperature Max. Application Temperature

35 F -65 F 220 F

Properties	Value
Stainless Steel	8.3 lbs/linear in.
Glass	6.7
Polyethylene	7.5

Corrugated 2.90 lbs./in.

Painted Metal 8.0 lbs/linear in.

**Loop Tack** 5.40 lbs./in2

### **Regulatory Approval**

RoHSProp65REACHYesNoYes

TPCHCPSIAULYesYesNo

Direct Food FDA 21 CFR 175.105, BfR XIV

No Yes

#### Liner

A bleached kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand die-cutting, marginal punching, perforating, fanfolding and refolding process while providing excellent dimensional stability.

No

Tensile MD Tensile CD

35 15

**Tear MD**50 **Tear CD**75

Description Value

Basis Weight 0

Caliper 3,4

#### **Regulatory Approval**

RoHSProp65REACHYesYesYes

TPCH CPSIA
Yes Yes

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

<sup>\*</sup>Please contact your sales representative for details

<sup>\*</sup>Please contact your sales representative for details

orders.us@beontag.com