

FSC ScandCoat MC SSP 713 K2



ITEM #F120002H0N000

Description

ScandCoat MC is a medium gloss machine coated paper with good whiteness. It is a versatile paper which is suitable for a very wide range of primary label work.

Developed for general colour printing, ScandCoat MC gives good colour lift and can be printed by flexography, rotary or flat-bed letterpress, offset lithography, screen process and can be foil blocked and varnished.

It can also be thermal transfer overprinted with suitable smudge resistant ribbons.

The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.

Facestock

ScandCoat MC is a medium gloss machine coated paper with good whiteness. It is a versatile paper which is suitable for a very wide range of primary label work. Developed for general color printing, ScandCoat MC gives good color lift and can be printed by flexography, rotary or flat-bed letterpress, offset lithography, screen process and can be foil blocked and varnished. It can also be thermal transfer overprinted with suitable smudge resistant ribbons.

Type

Paper

Properties

Value

Caliper

2.7 Mil

Regulatory Approval

RoHS

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

UL

No

FSC

Yes

*Please contact your sales representative for details

Adhesive

SSP713 has excellent initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Particularly good adhesion to cardboard, plastic and glass. Note: Not advised for labelling highly plasticised materials, eg: flexible PVC

Composition

Rubber

Type

Permanent

Application Temperature

8 F

Min. Application Temperature

-10 F

Max. Application Temperature

70 F

Typical Adhesion values**Properties****Value****Stainless Steel**

18N

Regulatory Approval**Food contact**

Complies with FDA175.105, BfR XIV.

FDA 21 CFR 175.105, BfR XIV

Yes

ISEGA approved for direct contact with dry and moist non-fatty foods

Yes

*Please contact your sales representative for details

Liner

ScandSil Kraft 66 (K2) is a bleached kraft backing with good lay-flat properties and dimensional stability.

Type

Paper

Description**Method****Value****Basis Weight**

ISO 536

66 ± 3g/m²**Caliper**

ISO 534

69 ± 4μ

*Please contact your sales representative for details

Final product

ScandCoat MC is a medium gloss machine coated paper with good whiteness. It is a versatile paper which is suitable for a very wide range of primary label work.

Developed for general colour printing, ScandCoat MC gives good colour lift and can be printed by flexography, rotary or flat-bed letterpress, offset lithography, screen process and can be foil blocked and varnished.

It can also be thermal transfer overprinted with suitable smudge resistant ribbons.

The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.

Format

Roll

Description**Value****Typical Caliper**

146 ± 10μ

Regulatory Approval

Certificate

The product is registered to SCS-COC-004802 FSC™ Mix credit.

Material Shelf Life

12 months stored at 20°C/50% RH

*Please contact your sales representative for details

Last update: 05/01/2024

ADDRESS:

Beontag

Pål Anders väg 4, 263 35

Höganäs, Sweden

+46 42 25 00 50

orders.scandstick@beontag.com