

Pressure-sensitive adhesives

Hot Melt Paper

GREEN FLUORESCENT / TR447 @ 1.4 Cwt. / 40#SCK L-3

ITEM #588

Facestock

A premium coated one side face stock in a bright fluorescent color with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting.

Type Paper			
Tensile MD 26 Lbs/in	Tensile CD 14 Lbs/in		
Tear MD 45 Grams	Tear CD 53 Grams		
Properties	Value		
Caliper	3.80 Mil		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	
*Please contact your sales representative for details			

Adhesive

A general purpose, removable rubber based emulsion adhesive featuring good initial tack and moderate adhesion. It has limited plasticizer, UV and solvent resistance. This is a standard removable adhesive for tape reels, computer disks and kids stickers.

Composition Hot Melt	Type Removable	Shear 40
Application Temperature 40 F	Min. Application Temperature 1 F	Max. Application Temperature 120 F
Properties	Value	
Stainless Steel	2.5 lbs/linear in.	
Glass	0.9	

Polyethylene	1.8		
Corrugated	1.00 lbs./in.		
Painted Metal	1.6 lbs/linear in.		
Loop Tack	1.50 lbs./in.		
Regulatory Approval			
RoHS	Prop65	REACH	
	Prop65 No	REACH Yes	
Yes	-		
Yes TPCH	No	Yes	
RoHS Yes TPCH Yes Direct Food	No CPSIA	Yes UL	

Liner

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type 5517342			
Tensile MD	Tensile CD		
34 Lbs/In	22 Lbs/In		
Tear MD	Tear CD		
32 Grams	34 Grams		
Description	Value		
Basis Weight	40 Lbs/Rm		
Caliper	2.5 Mil		
Regulatory Approval			
RoHS	Prop65	REACH	
Yes	Yes	Yes	

TPCH Yes	CPSIA Yes	
Direct Food No		
*Please contact your sales representative for details		

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

UL

No

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 222 Mound Avenue Miamisburg, OH 45342 <u>800-358-4448</u> orders.us@beontag.com