

# ScandMet S SSP713 HG0

## Description

ScandMet S is a bright silver metallised printing paper, that has been coated with a print receptive acrylic lacquer.

The material offers top print quality by all conventional print methods, like flexography, letterpress, offset and screen.

Note that special inks for non-absorbent materials should be used.

The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.

### Facestock

ScandMet S is a bright silver metallised printing paper, that has been coated with a print receptive acrylic lacquer. The material offers top print quality by all conventional print methods, like flexography, letterpress, offset and screen. Note that special inks for non-absorbent materials should be used.

### Type

Paper

Properties	Method	Value
Basis Weight	ISO 536	74 ± 3g/m <sup>2</sup>
Caliper	ISO 534	73 ± 5µ
Smoothness	ISO 5627	> 12900s

### Regulatory Approval

#### FSC

No

\*Please contact your sales representative for details

### Adhesive

SSP713 has excellent initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Particularly good adhesion to cardboard, plastic and glass. Note: Not advised for labelling highly plasticised materials, eg: flexible PVC

<b>Composition</b> Rubber	<b>Type</b> Permanent	<b>Application Temperature</b> 8 F
<b>Min. Application Temperature</b> -10 F	<b>Max. Application Temperature</b> 70 F	

## Typical Adhesion values

Properties	Value
------------	-------

Stainless Steel	18N
-----------------	-----

## Regulatory Approval

<b>Food contact</b> Complies with FDA175.105, BfR XIV.	<b>FDA 21 CFR 175.105, BfR XIV</b> Yes	<b>ISEGA approved for direct contact with dry and moist non-fatty foods</b> Yes
---	---	--

\*Please contact your sales representative for details

## Liner

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Description	Method	Value
<b>Basis Weight</b>	ISO 536	55 ± 3g/m <sup>2</sup>
<b>Caliper</b>	ISO 534	49 ± 3μ
<b>Transparency</b>	ISO 2469	50%

\*Please contact your sales representative for details

## Final product

ScandMet S is a bright silver metallised printing paper, that has been coated with a print receptive acrylic lacquer.

The material offers top print quality by all conventional print methods, like flexography, letterpress, offset and screen.

Note that special inks for non-absorbent materials should be used.

The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.

## Format

Roll

Description	Value
<b>Typical Caliper</b>	142 ± 10μ

## Regulatory Approval

### Material Shelf Life

12 months stored at 20°C/50% RH

\*Please contact your sales representative for details

Last update:

ADDRESS:  
Beontag  
Pål Anders väg 4, 263 35

Höganäs, Sweden

+46 42 25 00 50

[orders.scandstick@beontag.com](mailto:orders.scandstick@beontag.com)