

Pressure-sensitive adhesives

Acrylic

Paper

TECHNI-GLOSS II HIGH GLOSS / IP400 @ 1.7 Cwt. / 1.2 MIL PET L-3

ITEM #86576

Facestock

A premium cast coated C1S white high gloss paper with a smooth print surface that offers excellent receptivity and print characteristics. The 90% gloss rating provides for the desired wet look label graphics that product manufacturers desire to enhance sales activity.

Type

Paper

35 Grams

Tensile MD

25 Lbs/in

Tensile CD

Tensile CD

Tensile CD

Properties Value

Caliper 3.70 Mil

Opacity 90

Regulatory Approval

RoHSProp65REACHYesYesYes
TPCH
Yes
CPSIA
Yes
No

40 Grams

FSC No

*Please contact your sales representative for details

Adhesive

A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.

Composition	Туре	Shear
Acrylic	Permanent	80
Application Temperature	Min. Application Temperature	Max. Application Temperature
35 F	-65 F	200 F

Typical Adhesion values Properties	Value			
Stainless Steel	5.5 lbs/linear in.			
Glass	3.0			
Polyethylene	2.0			
Corrugated	1.45 lbs./in.	1.45 lbs./in. 3.0 lbs/linear in.		
Painted Metal	3.0 lbs/linear in.			
Loop Tack	5.00 lbs./in.			
Regulatory Approval				
RoHS	Prop65	REACH		
Yes	Yes	Yes		
ТРСН	CPSIA	Direct Food		
Yes	Yes	No		
Indirect Food				
Yes				

Liner

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Tensile MD	Tensile CD
30000	0
Tear MD	Tensile CD
0	0
0	0

Description	Value
Basis Weight	0
Caliper	1,2

Regulatory Approval

RoHS	Prop65	REACH
Yes	Yes	Yes
TDCU	CDCIA	

TPCH CPSIA
Yes Yes

Last update: 05/01/2024

^{*}Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 222 Mound Avenue Miamisburg, OH 45342

800-358-4448 orders.us@beontag.com