

TECHNI-GLOSS II HIGH GLOSS / TS585WS @ 1.6 Cwt.
/ 1.2 MIL PET L-3

ITEM #86574

Facestock

A premium cast coated C1S white high gloss paper with a smooth print surface that offers excellent receptivity and print characteristics. The 90% gloss rating provides for the desired wet look label graphics that product manufacturers desire to enhance sales activity.

Type

Paper

Tensile MD

25 Lbs/in

Tensile CD

0 Lbs/in

Tear MD

35 Grams

Tear CD

40 Grams

Properties

Value

Caliper

3.70 Mil

Opacity

90

Brightness

87

Regulatory Approval

RoHS

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

UL

No

FSC

No

*Please contact your sales representative for details

Adhesive

A specialty adhesive designed to adhere to slightly wet surfaces with good ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for hard to label substrates.

Composition

Acrylic

Type

Permanent

Shear

65

Application Temperature

Min. Application Temperature

Max. Application Temperature

| | | |
|---|--------------------|-------|
| -20 F | -65 F | 140 F |
| | | |
| Properties | Value | |
| Stainless Steel | 4.8 lbs/linear in. | |
| Glass | 3.2 | |
| Polyethylene | 2.0 | |
| Corrugated | 1.45 lbs./in. | |
| Painted Metal | 4.4 lbs/linear in. | |
| Loop Tack | 2.70 lbs./in. | |
| | | |
| Regulatory Approval | | |
| RoHS | Prop65 | REACH |
| Yes | No | Yes |
| TPCH | CPSIA | UL |
| Yes | Yes | No |
| Direct Food | Indirect Food | |
| No | Yes | |
| *Please contact your sales representative for details | | |

Liner

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

| | |
|--|------------------------------------|
| <div>Tensile MD</div> <div>30000</div> | <div>Tensile CD</div> <div>0</div> |
| <div>Tear MD</div> <div>0</div> | <div>Tear CD</div> <div>0</div> |

| Description | Value |
|--------------|-------|
| Basis Weight | 0 |
| Caliper | 1,2 |

Regulatory Approval

| | | |
|--------------------------------|----------------------------------|---------------------------------|
| <div>RoHS</div> <div>Yes</div> | <div>Prop65</div> <div>Yes</div> | <div>REACH</div> <div>Yes</div> |
| <div>TPCH</div> <div>Yes</div> | <div>CPSIA</div> <div>Yes</div> | |

*Please contact your sales representative for details

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag

222 Mound Avenue Miamisburg, OH 45342

[800-358-4448](tel:800-358-4448)

orders.us@beontag.com